

## 6.5" Two-Way In-Wall Loudspeaker



# R-5650-W

Sophisticated, yet uncomplicated, the Klipsch R-5650-W in-wall loudspeaker will forever change the way you view or listen to architectural audio. Whether used for home theater or stereo music applications, this high-quality and installer-friendly model challenges the performance of comparable stand alone speakers.

By featuring a 6.5-inch Cerametallic™ woofer cone, 1-inch titanium tweeter mated to a pivoting Tractrix® Horn, as well as treble and bass contour switches, there's no denying this speaker's natural precision, clarity and efficiency.

Available in a white finish, the R-5650-W can be paired with one of Klipsch's new installation kits (sold separately). Each of these revolutionary kit designs allow for increased mounting flexibility and incorporate a mud ring, wire tie and universal metal mesh wing for multi-position placement and a color-coded bracket for easy speaker size identification.

- Very high sensitivity and power handling
- Pivoting Tractrix Horn compression driver tweeter for clear sound in any location
- Treble and midbass attenuation switches and IR receiver knock out
- Single piece grille frame and rustproof aluminum grille

### SPECIFICATIONS

FREQUENCY RESPONSE	52Hz-20kHz ± 3dB
SENSITIVITY	93dB @ 1 watt/1 meter
NOMINAL IMPEDANCE	8 ohms
CROSSOVER FREQUENCY	2500Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE MATERIAL/TYPE	ABS/ Infinite baffle, front flush with wall
DRIVE COMPONENTS	Two-way system using one 1" (2.54cm) Titanium dome compression tweeter with a 6" (15.24cm) square 90° x 60° pivoting Tractrix® Horn and one 6.5" (16.51cm) aluminum cone woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	7.2 lbs. (3.25kg)
HEIGHT	14.3" (36.32cm)
WIDTH	9.3" (23.62cm)
MOUNTING DEPTH	3.75" (9.5cm)
CUTOUT DIMENSIONS	13" (33.02cm) x 8" (20.32cm)
FINISH	White
INSTALLATION KIT	IK-650-W (sold separately)

www.klipsch.com  
1-800-KLIPSCH

